

Safety Data Sheet (SDS)

		3	alety D	ata Sneet	. (303)		
			Sectior	n 1 – Identifica	tion		
1(a) Product Ide	entifier us	sed on Label: EA 7000	Alloy Grades	5			
1(b) Other mean	ns of iden	tification: EA 7050 All	oy, EA 7055 A	Alloy, EA 7149 Allo	y and EA 7175 Allo	у	
1(c) Recommen	ded use o	f the chemical and rest	rictions on us	e: Metal alloy for m	ultiple production us	ses	
1(d) Name, add ELLWOOD 7158 Hubba Hubbard, O) Aluminu ard Masur		one number: 3	330-534-8668			
1(e) Emergency	phone n	umber: 11-800-424-930	0 or CHEMTR	REC (Day or Night):	1-800-424-9300		
		Se	ection 2 – I	Hazard(s) Iden	tification		
not exempt as a considered a mi <u>SYSTEM OF CI</u> <u>New York and C</u> 2(b) Signal wor	n article u ixture and LASSIFIC Geneva, 20	ject to classification und under OSHA's Hazard C l a hazardous material. <u>CATION AND LABELL</u> <u>109</u> have been evaluated. statement(s), symbols	Communication Therefore, th ING OF CHE Refer to Secti and precaution	n Standard (29 CFR le categories of Hea <u>MICALS (GHS), Th</u> on 3, 8 and 11 for ac	1910.1200) due to alth Hazards as defined revised edition S	its downstream use, th fined in <u>"GLOBALLY</u> ST/SG/AC.10/30/Rev. 3	nus this product HARMONIZE
Hazard Symbol	Haza	ard Classification	Signal Word		Hazard S	Statement(s)	
		'arget Organ Toxicity Repeat Exposure - 1					ation exposure.
Precautionary S	tatement(s	s):					
	Preve			Response Storage/Disposal			isposal
Do not breathe dusts or fumes. Wash thoroughly after handling. Do not eat, drink or smoke when using this product.		Get medi	Get medical advice/attention if you feel unwell. Dispose of contents in accordance federal, state and local regulation				
2(c) Hazards no	t otherwi	se classified: None Kno	own				
2(d) Unknown a	cute toxi	city statement (mixture): None Know	'n			
		Section 3 -	- Composi	tion/Informati	on on Ingredi	ents	
3(a-c) Chemical	l name, co	ommon name (synonym	s), CAS numl	ber and other ident	ifiers, and concent	ration:	
Chemical Name			Alloy		CAS Number	EC Number	% weight*
Aluminum		EA 7050 Alloy, EA EA	A 7055 Alloy, E A 7175 Alloy	EA 7149 Alloy,	7429-90-5	231-072-3	85.9-91.4
Copper		EA 7050 Alloy, EA EA	A 7055 Alloy, E A 7175 Alloy	EA 7149 Alloy,	7440-50-8	231-159-6	1.2-2.6
Manganese			A 7175 Alloy		7439-96-5	231-105-1	0-2.9
Magnesium		EA 7050 A	Alloy, EA 7055	Alloy	7439-95-4	231-104-6	0-2.3
Zinc		EA 7050 Alloy, EA Ea	A 7055 Alloy, E A 7175 Alloy	EA 7149 Alloy,	7440-66-6	231-142-3	5.1-8.4
EC - European Com CAS - Chemical Abs	-		·				

* Percentages are expressed as typical ranges or maximum concentrations of trace elements for the purpose of communicating the potential hazards of the finished product.

"Commercial steel products contain small amounts of various elements in addition to those specified. These small quantities frequently referred to as "trace" or "residual" elements, generally originate in the raw materials used and/or are alloying metals. Individual trace elements vary in concentration by weight, and may include chromium, iron, silicon, titanium and zirconium.

Section 4 – First-aid Measures

4(a) Description of necessary measures:

• Inhalation: EA 7000 Alloy Grades as sold/shipped is not a likely form of exposure. If inhaled, call a poison center or doctor/physician

• Eye Contact: EA 7000 Alloy Grades as sold/shipped is not a likely form of exposure.



Section 4 – First-aid Measures (continued)

4(a) Description of necessary measures: (continued)

Skin Contact: EA 7000 Alloy Grades as sold/shipped is not a likely form of exposure.

Ingestion: EA 7000 Alloy Grades as sold/shipped is not a likely form of exposure.

4(b) Most important symptoms/effects, acute and delayed (chronic):

- Inhalation: EA 7000 Alloy Grades as sold/shipped is not likely to present an acute or chronic health effect.
- Eye: EA 7000 Alloy Grades as sold/shipped is not likely to present an acute or chronic health effect.
- Skin: EA 7000 Alloy Grades as sold/shipped is not likely to present an acute or chronic health effect.
- Ingestion: EA 7000 Alloy Grades as sold/shipped is not likely to present an acute or chronic health effect.

However, during further processing (welding, grinding, burning, etc.) individual components may illicit an acute or chronic health effect. Refer to Section 11-Toxicological Information.

4(c) Immediate Medical Attention and Special Treatment: None Known

Section 5 – Fire-fighting Measures

5(a) Suitable (and unsuitable) Extinguishing Media: Not Applicable for EA 7000 Alloy Grades as sold/shipped. Use extinguishers appropriate for surrounding materials.

5(b) Specific Hazards arising from the chemical: Not Applicable for EA 7000 Alloy Grades as sold/shipped. When burned, toxic smoke, fume and vapor may be emitted.

5(c) Special protective equipment and precautions for fire-fighters: Self-contained NIOSH approved respiratory protection and full protective clothing should be worn when fumes and/or smoke from fire are present. Heat and flames cause emittance of acrid smoke and fumes. Do not release runoff from fire control methods to sewers or waterways. Firefighters should wear full face-piece self-contained breathing apparatus and chemical protective clothing with thermal protection. Direct water stream will scatter and spread flames and, therefore, should not be used.

Section 6 - Accidental Release Measures

6(a) Personal Precautions, Protective Equipment and Emergency Procedures: Not Applicable for **EA 7000 Alloy Grades** as sold/shipped. For spills involving finely divided particles, clean-up personnel should be protected against contact with eyes and skin. If material is in a dry state, avoid inhalation of dust.

6(b) Methods and materials for containment and clean up: Not Applicable for **EA 7000** Alloy Grades as sold/shipped. Collect material in appropriate, labeled containers for recovery or disposal in accordance with federal, state, and local regulations. Follow applicable OSHA regulations (29 CFR 1910.120) and all other pertinent state and federal requirements.

Section 7 - Handling and Storage

7(a) Precautions for safe handling: Not Applicable for EA 7000 Alloy Grades as sold/shipped, however further processing (welding, burning, grinding, etc.) with the potential for generating high concentrations of airborne particulates should be evaluated and controlled as necessary. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in well-ventilated areas. Practice good housekeeping. Avoid breathing metal fumes and/or dust. Do not eat, drink or smoke when using this product. Cut resistant gloves and sleeves should be worn when working with steel products.

7(b) Conditions for safe storage, including any incompatibilities: Store away from acids and incompatible materials.

Section 8 - Exposure Controls / Personal Protection

8(a) Occupational Exposure Limits (OELs): EA 7000 Alloy Grades as sold/shipped in its physical form does not present an inhalation, ingestion or contact hazard, nor would any of the following exposure data apply. However, operations such as burning, welding (high temperature), sawing, brazing, machining, grinding, etc. may produce fumes and/or particulates. The following exposure limits are offered as reference for an experienced industrial hygienist to review.

Ingredients	OSHA PEL ¹	ACGIH TLV ²	NIOSH REL ³	IDLH ⁴
Aluminum	15 mg/m ³ (as Al aluminum oxide, metal & insoluble compounds,	1.0 mg/m ³ (as metal & insoluble compounds, respirable fraction ⁵)	10 mg/m ³ (as metal & insoluble compounds, total dust)	NE
	total dust) 5.0 mg/m ³ (as Al aluminum oxide,		5.0 mg/m ³ (as metal & insoluble compounds, respirable fraction)	
	metal & insoluble compounds, respirable fraction)		5.0 mg/m ³ (as Al, welding fumes & pyro powders)	
Copper	0.1 mg/m ³ (as fume, Cu) 1.0 mg/m ³ (as dusts & mists, Cu)	0.2 mg/m ³ (as fume) 1.0 mg/m ³ (as dusts & mists, Cu)	0.1 mg/m ³ (as fume, Cu) 1.0 mg/m ³ (as dusts & mists, Cu)	100 mg Cu/m ³
Manganese	"C" 5.0 mg/m ³ (as fume & inorganic compounds, as Mn)	0.02 mg/m ³ (as fume & inorganic compounds, as Mn, respirable fraction)	1.0 mg/m ³ (as fume & inorganic compounds, as Mn)	500 mg/m ³ (as Mn)
		0.1 mg/m ³ (as fume & inorganic compounds, as Mn, inhalable fraction ⁶)	"STEL" 3.0 mg/m ³ (as fume & inorganic compounds, as Mn)	



Section 8 - Exposure Controls / Personal Protection (continued)

8(a) Occupat	8(a) Occupational Exposure Limits (OELs) (continued):						
Ingredients	OSHA PEL ¹	ACGIH TLV ²	NIOSH REL ³	IDLH ⁴			
Magnesium	15 mg/m ³ (as magnesium oxide fume, total particulate)	10 mg/m ³ (as magnesium oxide, inhalable fraction)	NE	750 mg/m ³ (as magnesium oxide fume)			
Zinc and compounds	15 mg/m ³ (as zinc oxide, total dust) 5.0 mg/m ³ (as zinc oxide, respirable fraction & zinc oxide fume)	2.0 mg/m ³ (as zinc oxide, respirable fraction) "STEL" 10 mg/m ³ (as zinc oxide, respirable fraction)	5.0 mg/m ³ (as zinc oxide dust or fume) "STEL" 10 mg/m ³ (as zinc oxide fume) "C" 15 mg/m ³ (as zinc oxide dust)	500 mg/m ³ (as zinc oxide)			

NE - None Established

1. OSHA PELs (Permissible Exposure Limits) are 8-hour TWA (time-weighted average) concentrations unless otherwise noted. A ("C") designation denotes a ceiling limit, which should not be exceeded during any part of the working exposure unless otherwise noted. A Short Term Exposure Limit (STEL) is defined as a 15-minute exposure, which should not be exceeded at any time during a workday. An Action level (AL) is used by OSHA and NIOSH to express a health or physical hazard. They indicate the level of a harmful or toxic substance/activity, which requires medical surveillance, increased industrial hygiene monitoring, or biological monitoring. Action Levels are generally set at one half of the PEL but the actual level may vary from standard to standard. The intent is to identify a level at which the vast majority of randomly sampled exposures will be below the PEL.

- Threshold Limit Values (TLV) established by the American Conference of Governmental Industrial Hygienists (ACGIH) are 8-hour TWA concentrations unless otherwise noted. ACGIH TLVs are for guideline purposes only and as such are not legal, regulatory limits for compliance purposes. DSEN – May cause dermal sensitization. This notation is used to indicate the potential for dermal sensitization resulting from the interaction of an absorbed agent and ultraviolet light (i.e. photosensitization). RSEN – May cause respiratory sensitization.
- 3. The National Institute for Occupational Safety and Health Recommended Exposure Limits (NIOSH-REL)- Compendium of Policy and Statements. NIOSH, Cincinnati, OH (1992). NIOSH is the federal agency designated to conduct research relative to occupational safety and health. As is the case with ACGIH TLVs, NIOSH RELs are for guideline purposes only and as such are not legal, regulatory limits for compliance purposes.
- 4. The "immediately dangerous to life or health air concentration values (IDLHs)" are used by NIOSH as part of the respirator selection criteria and were first developed in the mid-1970's by NIOSH. The Documentation for Immediately Dangerous to Life or Health Concentrations (IDLHs) is a compilation of the rationale and sources of information used by NIOSH during the original determination of 387 IDLHs and their subsequent review and revision in 1994. Ca is designated as carcinogen.
- 5. Respirable fraction. The concentration of respirable dust for the application of this limit is to be determined from the fraction passing a size-selector with the characteristics defined in ACGIH 2023 TLVs [®] and BEIs [®] Appendix D, paragraph C.

6. Inhalable fraction. The concentration of inhalable particulate for the application of this TLV is to be determined from the fraction passing a size-selector with the characteristics defined in the ACGIH 2023 TLVs [®] and BEIs [®] (Biological Exposure Indices) Appendix D, paragraph A.

8(b) Appropriate Engineering Controls: Use controls as appropriate to minimize exposure to metal fumes and dusts during handling operations. Provide general or local exhaust ventilation systems to minimize airborne concentrations. Local exhaust is necessary for use in enclosed or confined spaces. Provide sufficient general/local exhaust ventilation in pattern/volume to control inhalation exposures below current exposure limits.

8(c) Individual Protection Measures:

• **Respiratory Protection:** Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, use only a NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. Concentration in air of the various contaminants determine the extent of respiratory protection needed. Half-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 10 times the exposure limit. Full-face, negative-pressure, air-purifying negative-pressure and powered air respirators is limited. Use a positive-pressure-demand, full-face, supplied air respirator or self-contained breathing apparatus (SCBA) for concentrations above 50 times the exposure limit. If exposure is above the IDLH (Immediately dangerous to life or health) for any of the constituents, or there is a possibility of an uncontrolled release or exposure levels are unknown, then use a positive-demand, full-face, supplied air respirator with escape bottle or SCBA.

Warning! Air-purifying respirators both negative-pressure and powered-air do not protect workers in oxygen-deficient atmospheres.

- Eyes: Wear appropriate eye protection to prevent eye contact. For operations which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulates, use safety glasses to prevent eye contact. Contact lenses should not be worn where industrial exposure to this material are likely. Use safety glasses or goggles as required for welding, burning, sawing, brazing, grinding or machining operations.
- Skin: Wear appropriate personal protective clothing to prevent skin contact. Cut resistant gloves and sleeves should be worn when working with steel products. For operations which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulates, use protective clothing, and gloves to prevent skin contact. Protective gloves should be worn as required for welding, burning or handling operations. Contaminated work clothing must not be allowed out of the workplace.
- Other protective equipment: An eyewash fountain and deluge shower should be readily available in the work area.

Section 9 - Physical and Chemical Properties			
9(a) Appearance (physical state, color, etc.): Solid, Metallic, Silver, 9(j) Upper/lower Flammability or Explosive Limits: NA Gray			
9(b) Odor: Odorless	9(k) Vapor Pressure: NA		
9(c) Odor Threshold: NA	9(1) Vapor Density (Air = 1): NA		
9(d) pH: NA	9(m) Relative Density: 2.80-2.86 g/cm ³		
9(e) Melting Point/Freezing Point: 477 - 635 °C/ 890.6 -1,175 °F	9(n) Solubility(ies): Insoluble		



EA 7000 Alloy Grades

Section 9 - Physical and Chemical Properties (continued)

9(f) Initial Boiling Point and Boiling Range: ND

9(g) Flash Point: NA

9(h) Evaporation Rate: NA

9(i) Flammability (solid, gas): Non-flammable, non-combustible NA - Not Applicable

ND - Not Determined for product as a whole

Section 10 - Stability and Reactivity

10(a) Reactivity: Not Determined (ND) for product in a solid form. Do not use water on molten metal.

10(b) Chemical Stability: Steel/Aluminum products are stable under normal storage and handling conditions.

10(c) Possibility of hazardous reaction: None Known

10(d) Conditions to Avoid: Storage with strong acids or calcium hypochlorite.

10(e) Incompatible Materials: Will react with strong acids to form hydrogen. Iron oxide dusts in contact with calcium hypochlorite evolve oxygen and may cause an explosion.

10(f) Hazardous Decomposition Products: Thermal oxidative decomposition of steel products can produce fumes containing oxides of iron and manganese as well as other alloying elements.

Section 11 - Toxicological Information

11 Information on toxicological effects: The following toxicity data has been determined for EA 7000 Alloy Grades when further processed using the information available for its components applied to the guidance on the preparation of an SDS under the GHS requirements of OSHA and the EU CPL:

Hazard Classification	Hazard Category				Hazard Statement	
Hazaru Classification	EU	OSHA	Symbols Word	Hazar u Statement		
STOT following Repeated Exposure (covers Categories 1 and 2)	NA*	1 ^j		Danger	Causes damage to lungs and central nervous system through prolonged or repeated inhalation exposure.	

* Not Applicable - Semi-formed steel/aluminum products are considered articles under Reach regulation (REACH REGULATION (EC) No 1907/2006) and are not subject to classification under CLP regulation (REGULATION (EC) No 1272/2008).

Toxicological data listed below are presented regardless to classification criteria. Individual hazard classification categories where the toxicological information has met or exceeded a classification criteria threshold are listed above.

a. No LC_{50} or LD_{50} has been established for **EA 7000 Alloy Grade**. The following data has been determined for the components:

- Aluminum: Rat LD₅₀ > 15.9 g/kg (REACH)
- **Copper:** Rat LD₅₀ = 481 mg/kg (REACH) Rat LD₅₀ > 2500 mg/kg (REACH)
- Manganese: Rat LD₅₀ > 2000 mg/kg (REACH) Rat LD₅₀ > 9000 mg/kg (NLM Toxnet)
- b. No Skin (Dermal) Irritation data available for EA 7000 Alloy Grade as a mixture or its components. The following data has been determined for the components:
 - Magnesium Dioxide: Severe skin irritant in human (HSDB).
- c. No Eye Irritation data available for EA 7000 Alloy Grade as a mixture or its components. The following data has been determined for the components:
 - Magnesium dioxide: Severe eye irritant in human (HSDB).
 - Silicon: Slight eye irritation in rabbit protocol.
- d. No Skin (Dermal) Sensitization data available for EA 7000 Alloy Grade as a mixture or its components
- e. No Respiratory Sensitization data available for EA 7000 Alloy Grade as a mixture or its components.
- f. No Germ Cell Mutagenicity data available for EA 7000 Alloy Grade as a mixture or its components
- g. Carcinogenicity: IARC, NTP, and OSHA do not list EA 7000 Alloy Grade as carcinogens. The following Carcinogenicity information was found for the components:
 - Aluminum (metal and insoluble compounds): IARC-1 (production), carcinogen to humans; ACGIH TLV-A4, not classifiable as a human carcinogen
 - Magnesium (oxide): ACGIH TLV-A4, not classifiable as a human carcinogen
 - Welding Fumes (not otherwise specified): IARC-1, carcinogen to humans; NIOSH-Ca, potential occupational carcinogen.
 - Manganese (inorganic compounds, as Mn): ACGIH TLV-A4, not classifiable as a human carcinogen; EPA-D, not classifiable as to human carcinogenicity
 - Manganese (fume, as Mn): ACGIH TLV-A4, not classifiable as a human carcinogen; EPA-D, not classifiable as to human carcinogenicity

9(o) Partition Coefficient n-octanol/water: ND9(p) Auto-ignition Temperature: NA9(q) Decomposition Temperature: ND

9(r) Viscosity: NA



Section 11 - Toxicological Information (continued)

11 Information on toxicological effects (continued):

- g. Carcinogenicity (continued):
 - Zinc (oxide): EPA-II, inadequate information to assess carcinogenic potential & EPA-D not classifiable as to human carcinogenicity & EPA-I, Data are Inadequate for an Assessment of Human Carcinogenic Potential
 - Zinc (oxide, fume): EPA-II, inadequate information to assess carcinogenic potential; EPA-D, not classifiable as to human carcinogenicity & EPA-I, Data are Inadequate for an Assessment of Human Carcinogenic Potential
- h. No Toxic Reproduction data available for EA 7000 Alloy Grade as a mixture or its components
- i. No Specific Target Organ Toxicity (STOT) following a Single Exposure data available for EA 7000 Alloy Grade as a mixture or its components
 - Iron: Irritating to respiratory tract.
- j. No Specific Target Organ Toxicity (STOT) following Repeated Exposure data was available for **EA 7000 Alloy Grade** as a mixture. The following STOT following Repeated Exposure data was found for the components:
 - Aluminum (metal and insoluble compounds): Repeated exposure associated with Asthma, Fibrosis in lungs and encephalopathy in humans.
 - Copper: Target organs affected Skin, eyes liver, kidneys and respiratory tract.
 - Manganese: Inhalation of metal fumes Degenerative changes in human Brain; Behavioral: Changes in motor activity and muscle weakness (Whitlock *et al.*, 1966).

The above toxicity information was determined from available scientific sources to illustrate the prevailing posture of the scientific community. The scientific resources includes: The American Conference of Governmental Industrial Hygienist (ACGIH) Documentation of the Threshold Limit Values (TLVs) and Biological Exposure indices (BEIs) with Other Worldwide Occupational Exposure Values 2023, The International Agency for Research on Cancer (IARC), The National Toxicology Program (NTP) updated documentation, the World Health Organization (WHO) and other available resources, the International Uniform Chemical Information Database (IUCLID), European Union Risk Assessment Report (EU-RAR), Concise International Chemical Assessment Documents (CICAD), European Union Scientific Committee for Occupational Exposure Limits (EU-SCOEL), Agency for Toxic Substances and Disease Registry (ATSDR), Hazardous Substance Data Bank (HSDB), and International Programme on Chemical Safety (IPCS), European Union Classification, Labeling and Packaging. (EU CPL), Regulation on Registration, Evaluation, Authorization and Restriction of Chemicals (REACH), International Uniform Chemical Information Database (IUCLID), TOXicology Data NETwork (TOXNET), European Risk Assessment Reports (EU RAR).

The following health hazard information is provided regardless to classification criteria and is based on the individual component(s) and potential resultant components from further processing:

Acute Effects:

- Inhalation: Excessive exposure to high concentrations of metal dust may cause irritation to the eyes, skin and mucous membranes of the upper respiratory tract. Excessive inhalation of fumes of freshly formed metal oxide particles sized below 1.5 micrometer and usually between 0.02-0.05 micrometers from many metals can produce an acute reaction known as "metal fume fever". Symptoms consist of chills and fever (very similar to and easily confused with flu symptoms), metallic taste in the mouth, dryness and irritation of the throat followed by weakness and muscle pain. The symptoms come on in a few hours after excessive exposures and usually last from 12 to 48 hours. Long-term effects from metal fume fever have not been noted. Freshly formed oxide fumes of copper have been associated with causing metal fume fever.
- Eye: Excessive exposure to high concentrations of metal dust may cause irritation to the eyes.
- Skin: Skin contact with metal dusts may cause irritation or sensitization, possibly leading to dermatitis. Skin contact with metallic fumes and dusts may cause physical abrasion.
- Ingestion: Ingestion of harmful amounts of this product as distributed is unlikely due to its solid insoluble form. Ingestion of metal dust may cause nausea or vomiting.

Acute Effects by component:

- Aluminum oxide: Inhalation may cause cough.
- Manganese Oxide: Manganese oxide is harmful if swallowed.
- Magnesium oxide: Headache, cough, sweating, nausea and fever may be caused by exposure to freshly formed fumes. The symptoms of metal fume fever do not become manifest until 4-12 hours after exposure.
- Copper and copper oxides: Copper may cause allergic skin reaction. Copper oxide is harmful if swallowed, causes skin and eye irritation, and may cause an allergic skin reaction.
- Zinc and zinc oxides: Not Reported/ Not Classified
- Iron and iron oxides: Iron is harmful if swallowed, causes skin irritation, and causes eye irritation. Contact with iron oxide has been reported to cause skin irritation and serious eye damage. Particles of iron or iron compounds, which become imbedded in the eye, may cause rust stains unless removed fairly promptly.

Delayed (chronic) Effects by component:

- Aluminum Oxide: Considered to be an inert or nuisance dust.
- Manganese Oxides: Chronic exposure to high concentrations of manganese fumes and dusts may adversely affect the central nervous system with
 symptoms including languor, sleepiness, weakness, emotional disturbances, spastic gait, mask-like facial expression and paralysis. Animal studies
 indicate that manganese exposure may increase susceptibility to bacterial and viral infections. Occupational overexposure (Manganese) is a
 progressive, disabling neurological syndrome that typically begins with relatively mild symptoms and evolves to include altered gait, fine tremor, and
 sometimes, psychiatric disturbances. May cause damage to lungs with repeated or prolonged exposure. Neurobehavioral alterations in worker
 populations exposed to manganese oxides include: speed and coordination of motor function are especially impaired.



Section 11 - Toxicological Information (continued)

11 Information on toxicological effects (continued):

Delayed (chronic) Effects by component: (continued)

- Magnesium Oxide: Irritation of eyes, nose, and throat. Symptoms may include dryness of nose and mouth, cough, feeling of weakness, tightness of chest, muscular pain, chills, fever, headache, nausea, and vomiting.
- **Copper:** Inhalation of high concentrations of freshly formed oxide fumes and dusts of copper can cause metal fume fever. Chronic inhalation of copper dust has caused, in animals, hemolysis of the red blood cells, deposition of hemofuscin in the liver and pancreas, injury to lung cells and gastrointestinal symptoms.
- Zinc and zinc oxides: Zinc dusts are a low health risk by inhalation and should be treated as a nuisance dust. Inhalation of zinc oxide fumes may cause metal fume fever, which is characterized by flu-like symptoms with metallic taste, fever, chills, cough, weakness, chest pain, muscle pain and increased white blood cell count.
- Iron and iron oxides: Chronic inhalation of excessive concentrations of iron oxide fumes or dusts may result in the development of a benign pneumoconiosis, called siderosis, which is observable as an X-ray change. No physical impairment of lung function has been associated with siderosis. Inhalation of excessive concentrations of ferric oxide may enhance the risk of lung cancer development in workers exposed to pulmonary carcinogens.

Section 12 - Ecological Information

12(a) Ecotoxicity (aquatic & terrestrial): No Data Available for EA 7000 Alloy Grade as sold/shipped. However, individual components of the product when processed have been found to be toxic to the environment. Metal dusts may migrate into soil and groundwater and be ingested by wildlife as follows:

• Zinc Oxide: EU RAR lists as Category 1 Very toxic to aquatic life with long lasting effects.

12(b) Persistence & Degradability: No Data Available for EA 7000 Alloy Grade as sold/shipped or individual components.

12(c) Bioaccumulative Potential: No Data Available for EA 7000 Alloy Grade as sold/shipped or individual components.

12(d) Mobility (in soil): No data available for EA 7000 Alloy Grade as sold/shipped. However, individual components of the product have been found to be absorbed by plants from soil.

12(e) Other adverse effects: None Known

Additional Information:

Hazard Category: Category 1

Signal Word: Warning

Hazard Symbol:

Hazard Statement: Very Toxic to aquatic life with long lasting effects.

Section 13 - Disposal Considerations

Disposal: Dispose of in accordance with Local, State, Federal and International regulations. Observe safe handling precautions.

Container Cleaning and Disposal: Follow Local, State, Federal and International regulations. Observe safe handling precautions

Please note this information is for EA 7000 Alloy Grade in its original form. Any alterations can void this information.

Section 14 - Transport Information

14 (a-g) Transportation Information:

US Department of Transportation (DOT) under 49 CFR 172.101 does not regulate **EA 7000 Alloy Grade** as a hazardous material. All federal, state, and local laws and regulations that apply to the transport of this type of material must be adhered to.

Section 15 - Regulatory Information

Regulatory Information: *The following listing of regulations relating to an Ellwood Aluminum product may not be complete and should not be solely relied upon for all regulatory compliance responsibilities.* This product and/or its constituents are subject to the following regulations:

OSHA Regulations: Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-2, Z-3): The product, **EA 7000 Alloy Grade** as a whole is not listed. However, individual components of the product are listed: Refer to Section 8, Exposure Controls and Personal Protection.

EPA Regulations: The product, EA 7000 Alloy Grade is not listed as a whole. However, individual components of the product are listed	d:
--	----

Regulations
SARA 313, TSCA, SDWA
CERCLA, CWA, SARA 313, TSCA, SDWA
TSCA
CERCLA, CWA, SARA 313, TSCA
SARA 313, TSCA
TSCA, SDWA



EA 7000 Alloy Grades

Section 15 - Regulatory Information

EPA Regulations (continued):

11	1 /	•	ains the following toxic chemicals subject to the reporting t-to-Know Act and 40 CFR part 372:
CAS #	Chemical Name	Percent by Weight	
7429-90-5	Aluminum	85.9-91.4	
7440-50-8	Copper	1.2-2.6	
7439-96-5	Manganese	0-2.9	
7439-95-4	Magnesium	0-2.3	
7440-66-6	Zinc	5.1-8.4	

Regulations Key:

CAA Clean Air Act (42 USC Sec. 7412; 40 CFR Part 61 [As of: 8/18/06])

CERCLA Comprehensive Environmental Response, Compensation and Liability Act (42 USC Secs. 9601(14), 9603(a); 40 CFR Sec. 302.4, Table 302.4, Table 302.4 and App. A)

CWA Clean Water Act (33 USC Secs. 1311; 1314(b), (c), (e), (g); 136(b), (c); 137(b), (c) [as of 8/2/06])

RCRA Resource Conservation Recovery Act (42 USC Sec. 6921; 40 CFR Part 261 App VIII)

SARA Superfund Amendments and Reauthorization Act of 1986 Title III Section 302 Extremely Hazardous Substances (42 USC Secs. 11023, 13106; 40 CFR sec. 372.65) and Section 313 Toxic Chemicals (42 USC Secs. 11023, 13106; 40 CFR Sec. 372.65 [as of 6/30/05])

TSCA Toxic Substance Control Act (15 U.S.C. s/s 2601 et seq. [1976]) SDWA Safe Drinking Water Act (42 U.S.C. s/s 300f et seq. [1974])

State Regulations: The product, EA 7000 Alloy Grade as a whole is not listed in any state regulations. However, individual components of the product are listed in various state regulations:

Pennsylvania Right to Know: Contains regulated material in the following categories:

- Hazardous Substances: Aluminum, Copper, Magnesium, Zinc, Zinc (compounds)
- Environmental Hazards: Aluminum, Copper, Zinc, Zinc (compounds)
- Special Hazardous Substance: Aluminum
- California Prop.

65:

WARNING: The product, **EA 7000 Alloy Grade** can expose you to chemicals including chromium (hexavalent chromium compounds), which is known to the State of California to cause cancer and to cause reproductive toxicity. For more information go to <u>www.P65Warnings.ca.gov</u>.

New Jersey: Contains regulated material in the following categories:

- Hazardous Substance: Aluminum, Copper, Magnesium, Zinc, Zinc (compounds)
- Environmental Hazards: Copper, Zinc, Zinc (compounds)
- Special Hazardous Substance: Aluminum
- Minnesota: Zinc, Zinc (compounds)

Massachusetts: Aluminum, Copper (compounds), Magnesium, Zinc, Zinc (compounds)

Other Regulations:

WHMIS Classification (Canadian): The product, EA 7000 Alloy Grade is not listed as a whole. However individual components are listed.

Ingredients	WHMIS Classification		
Aluminum	Not Applicable		
Copper	Acute oral toxicity – oral – Category 4; Combustible dusts*		
Magnesium	Flammable Solids – Category 2		
Manganese	Reproductive toxicity - Category 2; Specific target organ toxicity - repeated exposure - Category 1; Combustible dusts*		
Iron	Combustible dusts - Category 1 (may form combustible dust concentrations in air)		
Zinc	No information		
Silicon	Flammable solids - Category 2 (The classification "Flammable solids" refers to the amorphous form of silicon powder);		
	Combustible dusts**		

* This product could belong to the hazard class "Combustible dust", based on various factors related to the combustibility and explosiveness of its dust, including composition, shape and size of the particles.

** This product belongs to the hazard class "Combustible dust" if 5% or more by weight of its composition has a particle size < 500 µm.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

Section 16 - Other Information

Prepared By: Ellwood Aluminum Original Issue Date: 12/29/2023

Revised Date: Original



Section 16 - Other Information (continued)

Additional Information:

Hazardous Material Identification System (HMIS) Classification

Health Hazard	1
Fire Hazard	0
Physical Hazard	0

 $\rm HEALTH=$ 1, Denotes possible chronic hazard if airborne dusts or fumes are generated Irritation or minor reversible injury possible.

FIRE= 0, Materials that will not burn.

PHYSICAL HAZARD= 0, Materials that are normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosives.

ABBREV	/IATIONS/ACRONYMS:			
ACGIH	American Conference of Governmental Industrial Hygienists			
BEIs	Biological Exposure Indices			
CAS	Chemical Abstracts Service			
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act			
CLP	Classification, Labelling and Packaging			
CFR	Code of Federal Regulations			
CNS	Central Nervous System			
GI, GIT	Gastro-Intestinal, Gastro-Intestinal Tract			
HMIS	Hazardous Materials Identification System			
IARC	International Agency for Research on Cancer			
LC50	Median Lethal Concentration			
LD50	Median Lethal Dose			
LD Lo	Lowest Dose to have killed animals or humans			
LEL	Lower Explosive Limit			
LOEL	Lowest Observed Effect Level			
LOAEC	Lowest Observable Adverse Effect Concentration			
µg/m ³	microgram per cubic meter of air			
mg/m ³	milligram per cubic meter of air			
mppcf	million particles per cubic foot			
MSHA	Mine Safety and Health Administration			
NFPA	National Fire Protection Association	1		

National Fire Protection Association (NFPA)



HEALTH = 1, Exposure could cause irritation but only minor residual injury even if no treatment is given.

FLAMMABILIY = 0, Materials that will not burn.

INSTABILITY = 0, Normally stable, even under fire exposure conditions, and are not reactive with water.

NIF	No Information Found		
NIOSH	National Institute for Occupational Safety and Health		
NTP	National Toxicology Program		
ORC	Organization Resources Counselors		
OSHA	Occupational Safety and Health Administration		
PEL	Permissible Exposure Limit		
PNOR	Particulate Not Otherwise Regulated		
PNOC	Particulate Not Otherwise Classified		
PPE	Personal Protective Equipment		
ppm	parts per million		
RCRA	Resource Conservation and Recovery Act		
REACH	Regulation on Registration, Evaluation, Authorization and Restriction of Chemicals		
RTECS	Registry of Toxic Effects of Chemical Substances		
SARA	Superfund Amendment and Reauthorization Act		
SCBA	Self-contained Breathing Apparatus		
SDS	Safety Data Sheet		
STEL	Short-term Exposure Limit		
TLV	Threshold Limit Value		
TWA	Time-weighted Average		
UEL	Upper Explosive Limit		

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

EA 7000 Alloy Grade

Signal Word: WARNING



HAZARD STATEMENTS:

May cause damage to lungs through prolonged or repeated inhalation exposure.

PRECAUTIONARY STATEMENTS

Do not breathe dusts or fumes. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. If exposed, concerned: Call a poison center or doctor/physician. Dispose of contents in accordance with federal, state and local regulations. Store locked up.

SDS ID No.: EA 7000 Alloy Grade ELLWOOD Aluminum 7158 Hubbard Masury Road Hubbard, OH 44425 General Information: Phone: 330-534-8668 CHEMTREC (Day or Night): 1-800-424-9300 Original Issue Date: 12/11/2023

Revised: Original